

Horizontal Multistage Pumps (HMS)

FEATURES

Maintenance Free
High Operating Efficiency
Regid Construction
Anti corrosive coating on the CI parts
Free from rust and corrosion
Low Noise

OPTIONS

Automatic start / stop when
equipped with pressure control Booster
system for domestic water supply

APPLICATIONS

Pressure boosting systems
Domestic water supply systems
Cooling systems
Small Industrial water supply systems
Irrigation systems
RO Plants
Water treatment, Water purification



HMS SS Model

Impeller / Diffuser / Suction / Delivery : SS AISI 304.
Shaft : AISI 410.

Special Mechanical Seal.

Available only in 1.0 HP and 1.5 HP.
This pump is suitable for pumping
water hot and cold / milk / chemical.



S. No.	HP	Stage	TYPE	Pipe Size (Suction)	Pipe Size (Delivery)	m ³ /h l/min	0	1.2	2.4	3.6	4.8	6.0	7.2	8.4
							0	20	40	60	80	100	120	140
1.	0.8	0.60	BHMS008	25mm	25mm	Head / m	30	25	21	17	6			
2.	1.0	0.75	BHMS010	25mm	25mm	Head / m	40	35	30	26	16	6		
3.	1.5	1.1	BHMS015L	25mm	25mm	Head / m	50	41	37	33	29	24	18	6
4.	1.5	1.1	BHMS015H	25mm	25mm	Head / m	60	52	47	43	37	30	24	14
5.	2.0	1.5	BHMS200	25mm	25mm	Head / m	70	51	53	48	41	38	29	20

The above performances are based on a means supply voltage of 220 V - 1 ph 50 Cycles.